

CAT5E Patch Panel

Model: PP-C5-**

Application

CoreTECH RJ45 CAT5E UTP 24 ports patch panel utilizes PCB technology with rear cable management to provide excellent performance, all-in-one and economic solution for cross cross and direct connection inside management room.

Physical Parameters

Frame Material: Corrosion resistant steel Contact: Phosphor bronze, Gold plating

Termination Contact: Phosphor bronze, Nickel plating

Mechanical Parameters

Contact: Comply with FCC68-F & IEC-60603-7

Plug insertion life: 750 cycle min Conductor Gauge: 22-24AWG

Electrical Parameters

Insulation resistance: 500M ohms min, 100VDC Dielectric Withstand Voltage: 1000V DC/AC, 60HZ

Current Rating: 1.5Amp max

Contact resistance: 20 milli ohms max

Application Environment

Storage Temperature: -40~60°C Operating Temperature: -10~50°C Relative Humidity: 93% max

Cat Se

Feature and Benefits

- 1.PCB.110 IDC insertion
- 2.Provide installation and fixed accessories

Rear cable management provides good protection for horizontal cable with nylon tie

- 3.T568A & T568B color coding, easily cable termination
- 4. Every port with clearly label
- 5.Directly installed in 19" rack or cabinet
- 6.RJ45 180 degree keystone jack is more suitable for installation on patch panel