


Zip Duplex Fiber Optic Indoor Cable



Application

- Adopted to indoor distribution.
- As pigtail of communication equipment.
- Suitable for communication equipment served.
- Can be installed conveniently and pirated simply.

Characteristics

- Height strength kevlar yarn member.
- High quality tight buffered or loose tube.
- Soft and easy to strip.
- Round construction.

Technical Parameters

Out sheath Diameter	Tight Buffer Diameter	Weight	Minimum allowable Tensile Strength (N)		Minimum allowable Crush Load (N/100mm)		Minimum Bending Radius (MM)		Storage temperature
			short term	long term	short term	long term	short term	long term	
(MM)	(MM)	(KG)							(°C)
1.6x3.4	0.6	4.80	150	80	500	100	20D	10D	-20+60
1.8x3.8	0.6	5.00	150	80	500	100	20D	10D	-20+60
2.0x4.2	0.9	7.00	150	80	500	100	20D	10D	-20+60
2.4x5.0	0.9	9.00	150	80	500	100	20D	10D	-20+60
2.8x5.8	0.9	11.50	150	80	500	100	20D	10D	-20+60
3.0x6.2	0.9	12.50	150	80	500	100	20D	10D	-20+60

Optical Characteristics

Fiber Sort	Multimode	G.651	A1a: 50/125	Graded-index fiber
			A1b: 62.5/125	
Singlemode	G.652 (A、 B、 C、 D)		B1.1: Conventional fiber	
	G.653		B2: Zero dispersion shifted	
	G.654		B1.2: Cut-off wavelength shifted	
	G.655		B4: Main technical data for positive dispersion shifted single-mode fiber	