

LC-LC Patch cord

Model: PCDMM-LC-LC/ PCDSM-LC-LC

Application

- Fiber optic data transmission
- CATV: Active device termination
- Local Area Networks (LANs)
- Telecommunication networks
- Wide Area Networks
- LAN (including FITL, FTTH and FTTD)



Availability

- Compliant with: Telcordia, IEC, GR-326-CORE
- Simplex & Duplex patch cord available
- Pigtail available

Specification

Type	Singlemode (UPC)	Singlemode (APC)	Multimode (UPC)
Insertion Loss	≤ 0.2 dB	≤ 0.1 dB	≥ 0.2 dB
Return Loss	≥ 50 dB	≥ 60 dB	≥ 35 dB
Exchangeability	≤ 0.2 dB	≤ 0.1 dB	≥ 0.2 dB
Operating Temperature	-40°C to +80°C	-40°C to +80°C	-40°C to +80°C

Ordering Information

- Optical fiber Patch cord, Pigtail & Fan-out
- LC/APC, LC/UPC, SM & MM (50/125 or 62.5/125)
- Simplex & Duplex patch cord
- Various boot color
- Diameter of cable: 0.9mm, 2.0mm, 3.0mm
- Material: PVC & LSZH Armoured
- Length: 1M 1.5M 3M 5M