

## ST-ST Patch cord

Model: PCDSM-ST-ST-3

### Application

- Fiber optic data transmission
- CATV: Active device termination
- Local Area Networks (LANs)
- telecommunication networks
- Wide Area Networks
- LAN (including FITL, FTTH and FTTD)



### Availability

- Compliant with: Telcordia, IEC, GR-326-CORE
- Simplex & Duplex patch cord available
- Pigtail available

### Specification

| Type                  | Singlemode (UPC) | Singlemode (APC) | Multimode (UPC) |
|-----------------------|------------------|------------------|-----------------|
| Insertion Loss        | $\leq 0.2$ dB    | $\leq 0.1$ dB    | $\geq 0.2$ dB   |
| Return Loss           | $\geq 50$ dB     | $\geq 60$ dB     | $\geq 35$ dB    |
| Exchangeability       | $\leq 0.2$ dB    | $\leq 0.1$ dB    | $\geq 0.2$ dB   |
| Operating Temperature | -40°C to +80°C   | -40°C to +80°C   | -40°C to +80°C  |

### Ordering Information

- ST/APC, ST/UPC, SM & MM (50/125 or 62.5/125)
- Simplex & Duplex patch cord
- Various boot color
- Diameter of cable: 0.9mm, 2.0mm, 3.0mm
- Material: PVC & LSZH Armoured
- Length: 1M, 1.5M, 3M, 5M .....